

EX78900G Series

Hardened Managed 8-Port Gigabit PoE++ and 4-Port 100/1G/2.5G SFP Ethernet Switch



Highlight

+ 2.5GbE High Bandwidth and Scalability

- 8 x 10/100/1000BASE-T(X) ports for high bandwidth connections
- Up to 4 tri-speed 100/1000/2500BASE SFP uplink ports for fiber connections
- Full capacity switching running at full duplex

+ Hardened-Grade for Non-Ventilated & Harsh Environments

- Wide operating temperature range -40 to 75°C (-40 to 167°F)
- Fanless operation
- High impact, thermal shock, and electrical noise resistance

+ PoE Features

- Backward compatible with IEEE 802.3af & IEEE 802.3at
- IEEE 802.3bt PoE with up to 90W per port; Max. 480W total power budget
- PoE watchdog monitors status of connected PoE devices

+ Support

- Complimentary technical support
- Free firmware upgrades and notifications
- Limited lifetime warranty

Overview

The EX78900G series represents EtherWAN's latest advancement in 2.5G Ethernet switch technology, featuring comprehensive Layer 2 and Layer 3 management functionalities. This 2.5G managed PoE switch, compactly DIN-rail mounted, supports up to 8 gigabit PoE ports, providing a maximum of 90W PoE power. It adheres to the IEEE 802.3bt protocol while maintaining compatibility with IEEE 802.3af and IEEE 802.3at standards, allowing for versatile PoE power delivery ranging from 15W, 30W, 60W to 90W per Ethernet port.

Additionally, the switch integrates up to 4 tri-rate 2.5G SFP uplink ports, providing adaptability with triple-speed options of 100Mbps, 1000Mbps, and 2500Mbps for flexible connectivity expansion. The EX78900G series is designed to offer networks in urban infrastructure, transportation, security, and other critical sectors the trifecta of flexibility, speed, and reliability.

EtherWAN — **"When Connectivity is Crucial."**

Features

+ Interface

CLI, Telnet, Web GUI

+ Management

Firmware Upgrade

Configuration Backup

DHCP Server/Client/Snooping/Relay

RMON (Remote Monitoring)

Port Mirroring

NTP (Network Time Protocol) Synchronization

LLDP (Link Layer Discovery Protocol)

IPv4/IPv6

SNMP v1/v2c/v3

+ Security

MAC Address Filtering

Enable/Disable Port

Storm Control

System logging

Remote Authentication through RADIUS and
TACACS+

Complex Password Support

Multi-User Login and Privileged Access
Management

SSH for CLI and Telnet Security

SSL and HTTPS for Web Security

ACL (Access Control List)

+ Quality of Service (QoS)

Priority Queues: 8 Queues per Port

Traffic Classification Based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin), and Strict Mode

Rate Limiting (Ingress/Egress)

+ Layer 2 Features

Auto-Negotiation for Port Speed and Duplex
Flow Control

IEEE 802.3x full duplex mode

Back-pressure half duplex mode

Redundant Protocols

IEEE 802.1D STP

IEEE 802.1w RSTP

IEEE 802.1s MSTP

ITU-T G.8032 Ethernet Ring

Protection Switch (ERPS)

VLANs

IEEE 802.1Q Tag VLANs

GVRP

GMRP

Link Aggregation

Static Trunk (8 groups)

IEEE 802.3ad LACP

IGMP Snooping v1/v2/v3

+ Layer 3 Features

IP Packet Routing

Maximum 512 hosts

Maximum 64 routes

Static routing

RIP v1/v2

OSPF v2

+ Software Properties and Performance

Switching Fabric

36Gbps

Forwarding Rate

26.78Mpps

Max VLANs
256 (4096 VID)

Jumbo Frame Size
9KB

MAC Table Size
16K

Packet Buffer Memory
512KB

Specifications

+ Interface

Ethernet

8 x 10/100/1000BASE-T(X)

2 or 4 x 100/1000/2500BASE SFP

Console

1 x RJ45

Config Backup

1 x USB (Type A Connector)

Alarm Contact

Relay output, current capacity 0.5A/48VDC

LED Indicators

Per Unit: Power 1, Power 2

Per Port: Link/Activity (Green)

Per PoE Port: PoE Status (Amber)

+ Technology

Standards

IEEE 802.3u 100BASE-TX/100BASE-FX

IEEE 802.3ab 1000BASE-T

IEEE 802.3ad link aggregation control

IEEE 802.3z 1000BASE-SX/1000BASE-LX

IEEE 802.3x full duplex and flow control

IEEE 802.1D STP

IEEE 802.1p QoS

IEEE 802.1Q Tag VLANs

IEEE 802.1s MSTP

IEEE 802.1w RSTP

IEEE 802.1x Radius

IEEE 802.1ab LLDP

IEEE 802.3az Energy-Efficient Ethernet (EEE)

IEEE 802.3af/at/bt Power over Ethernet

Forward/Filtering Rate

14,880pps for 10Mbps

148,809pps for 100Mbps

1,488,095pps for 1000Mbps

3,720,238pps for 2500Mbps

Processing Type

Store-and-forward

Auto-negotiation

Half-duplex back-pressure and full-duplex flow control

Auto MDI/MDIX

System Memory

1GB DDR3 SDRAM

Flash Storage

128MB

+ Power

Input

46-57VDC Redundant (Terminal block)**

** Connected powered devices (PDs) power input requirements:

IEEE 802.3 af (15W): 46 – 57 VDC

IEEE 802.3 at (30W): 52 – 57 VDC

IEEE 802.3 bt (Type 3: 60 Watts): 52 – 57 VDC

IEEE 802.3 bt (Type 4: 90 Watts): 54 – 57 VDC

Power Consumption

Max. 14W (without PoE)

Power Budget (Max.)

For EX78912G-0BT:

- 240 Watts

For EX78924G-0BT & EX78922G-0BT:

- 480 Watts up to operating temp. 70°C
- 400 Watts up to operating temp. 75°C

Protection

Reverse Polarity Protection

+ Physical

Casing Material

Metal

IP Rating

IP30

Dimensions

62 x 125 x 145mm (W x D x H)

Weight

0.75 kg (1.65 lbs)

Installation Type

DIN-rail mounting

+ Environmental

Operating Temp.

-40 to 75°C (-40 to 167°F)

Storage Temp.

-45 to 85°C (-49 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

MTBF

TBD

+ Regulatory

ISO

Manufactured in ISO-9001 facility

EMI

FCC Part 15B Class A

VCCI Class A

EN 61000-6-4

EMS

EN 61000-6-2

Safety

UL 62368

Traffic

NEMA TS2

Rail

EN 50121-4

Vibration

IEC 60068-2-6

Shock

IEC 60068-2-27

Free Fall

IEC 60068-2-31

+ Warranty

Length

Limited Lifetime

Details

www.etherwan.com/support/warranty-policy

+ What's Included

Device

Ethernet switch


Cables

1 Console cable

Installation

Mounting brackets, screws


Dimensions



Application


Software

[Network Management eVue™ Network Configuration and Monitoring Tool](#)
[Network Discovery eLite™ Network Discovery and IP Configuration Tool](#)



The screenshot shows the EtherWAN web interface. On the left, there is a 'Device List' table with columns for IP, System Name, and Group. On the right, there is a 'Topology' diagram showing a network of interconnected devices. Below these, there is a 'Latest Events' section with a table of recent system events.

Acknowledged	ID	Severity	Time	Service	Node	Message
✓	5107	Normal	6/28/2019, 9:50:35 AM	login	server	User 'admin' logged in.
✓	5106	Normal	6/27/2019, 10:00:50 AM	login	server	User 'admin' logged in.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Web 192.168.1.19 is down.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Telnet 192.168.1.19 is down.
✓	5104	Normal	6/24/2019, 1:12:34 PM	login	server	User 'admin' logged in.



The screenshot shows the eLite application window. It features a menu bar with 'List Server', 'Firmware', 'Configuration', and 'Help'. Below the menu is a toolbar with various icons. The main area contains a table with two columns: 'IP Address' and 'MAC Address'.

IP Address	MAC Address
192.168.50.22	00:e0:b3:50:22:00
192.168.50.31	00:e0:b3:50:31:00
192.168.50.72	00:e0:b3:50:72:00
192.168.50.55	00:e0:b3:50:55:00
192.168.50.23	00:e0:b3:50:23:00
192.168.50.73	00:e0:b3:50:73:00
192.168.50.44	00:e0:b3:50:44:00
192.168.50.64	00:e0:b3:50:64:00
192.168.50.43	00:e0:b3:50:43:00
192.168.50.62	00:e0:b3:50:62:00
192.168.50.71	00:e0:b3:50:71:00
192.168.50.24	00:e0:b3:50:24:00

Ordering Info

+ Model

EX78924G-0BT	8-port 10/100/1000BASE-T(X) PoE++ 90W + 4-port 100/1000/2500BASE SFP
EX78922G-0BT	8-port 10/100/1000BASE-T(X) PoE++ 90W + 2-port 100/1000/2500BASE SFP
EX78912G-0BT	4-port 10/100/1000BASE-T(X) PoE++ 90W + 4-port 10/100/1000BASE-T(X) + 2-port 100/1000/2500BASE SFP

+ Accessories

SFP Modules

Model Number	Transmission Speed	Mode	Distance	Operating Temperature	Wavelength	Connector Type	DDM
SFP2IS20M	2500Mbps	Single-mode	20km	-40 to 85°C	1310nm	Duplex LC	✓
SFP2IM2AM	2500Mbps	Multi-mode	160m	-40 to 85°C	850nm	Duplex LC	✓
SFP2XT1AM	2500Mbps	-	100m	-40 to 85°C	-	RJ-45	-
SFPGIM5AM	1000Mbps	Multi-mode	275/550m	-40 to 85°C	850nm	Duplex LC	✓
SFPGIM02M	1000Mbps	Multi-mode	2km	-40 to 85°C	1310nm	Duplex LC	✓
SFPGIS10M	1000Mbps	Single-mode	10km	-40 to 85°C	1310nm	Duplex LC	✓
SFPGIS20M	1000Mbps	Single-mode	20km	-40 to 85°C	1310nm	Duplex LC	✓
SFPGXT1AM	1000Mbps	-	100m	-40 to 85°C	-	RJ-45	-
EX-0155NSP-MB2L-A	100Mbps	Multi-mode	2km	-40 to 85°C	1310nm	Duplex LC	-
SFPMIS20M (DDM)	100Mbps	Single-mode	20km	-40 to 85°C	1310nm	Duplex LC	✓

For more SFP, please visit website: www.etherwan.com/products/sfp-fiber-transceiver

Industrial DIN-Rail Power Supplies

Model Number	Input Voltage	Output Voltage	Description	Operating Temperature
NDR-480-48	90 - 264VAC	48VDC	480W/10A DIN-Rail 48VDC Industrial Power Supply	-20 to 70°C
NDR-240-48	90 - 264VAC	48VDC	240W/5A DIN-Rail 48VDC-20 to 70°C Industrial Power Supply	-20 to 70°C
NDR-120-48	90 - 264VAC	48VDC	120W/2.5A DIN-Rail 48VDC Industrial Power Supply	-20 to 70°C


For more Power Supplies, please visit website: www.etherwan.com/products/din-rail-power-supply.

+ DIN-Rail Mounting Kits

Part Name	Description
-----------	-------------


KP-AA96-480

Image not found or type unknown




KP-G300

Image not found or type unknown



KR-BK71000

Image not found or type unknown



© EtherWAN Systems, Inc. All rights reserved. 20240311

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.