

# EX19082A

Unmanaged 8-Port Gigabit PoE Ethernet Switch



## Highlights

### + Power over Ethernet

Total PoE power budget of 240W to deliver sufficient power to all connected PoE devices

Overloading protection

Power and data over a single cable with gigabit speed capable of handling cameras with 4K resolution and higher and other high bandwidth devices

## Overview

EtherWAN's EX19082A is a 10-port Gigabit Power over Ethernet switch with high performance and features suited for small-business and commercial environments. The EX19082A is equipped with 8 10/100/1000BASE-T(X) PoE+ ports and 2 Gigabit uplink ports (1 TX + 1 SFP). With full wire speed throughput, port speeds up to gigabit for 4K cameras and higher, and a power budget of 240W, the EX19082A is the perfect solution for security networks.

EtherWAN — "When Connectivity is Crucial."

# Hardware Specifications

## + Interface

<b>Ethernet</b>	10/100/1000BASE-T(X): 8 PoE+ ports + 1 TX port 1000BASE SFP: 1 port
<b>LED Indicators</b>	Per Unit: Power Per Port PoE: Status Per Port Link: Link/Activity

## + Technology

<b>Standards</b>	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-SX/1000BASE-LX IEEE 802.3x Full duplex and flow control IEEE 802.3af Power over Ethernet (PoE) IEEE 802.3at Power over Ethernet (PoE+)
<b>Forward and Filtering Rate</b>	14,880pps for 10Mbps 148,880pps for 100Mbps 1,488,000pps for 1000Mbps
<b>Processing Type</b>	Store-and-Forward Auto-Negotiation Half-duplex back-pressure full-duplex flow control Auto MDI/MDIX
<b>Switching Fabric</b>	20Gbps
<b>MAC Table Size</b>	8K
<b>Packet Buffer Memory</b>	4Mb

## + Power

<b>Input</b>	100-240VAC, 50/60Hz
<b>Power Consumption</b>	Device: 23W (without PoE) PoE Power Budget: 240W

## + Physical

<b>Casing Material</b>	Metal
<b>Dimensions</b>	266 x 161 x 44mm (W x D x H) 10.5" x 6.34" x 1.73"
<b>Weight</b>	4lbs (1.8kg)
<b>Installation Type</b>	Rack mounting, Desktop

## + Environmental

<b>Operating Temp.</b>	0 to 50°C (32 to 122°F)
<b>Storage Temp.</b>	-10 to 70°C (14 to 158°F)
<b>Relative Humidity</b>	10% to 90% (non-condensing)

## + Regulatory

<b>ISO</b>	Manufactured in ISO-9001 facility
<b>EMI</b>	FCC Part 15 Class B
<b>Safety</b>	UL 60950-1


## + Warranty

<b>Length</b>	3 Years
<b>Details</b>	<a href="http://www.etherwan.com/support/warrantypolicy">www.etherwan.com/support/warrantypolicy</a>
<b>Safety</b>	UL 60950-1

## + What's Included

<b>Device</b>	Ethernet Switch
<b>Power</b>	AC power cord
<b>Documentation</b>	Quick Install Guide

## Dimensions



## Ordering Info

### + Model

**EX19082A** 8-port 10/100/1000BASE-T(X) PoE + 1-port 10/100/1000BASE-T(X) + 1-port 1000BASE SFP

