

EX73000 Series

Hardened Managed 16-port 10/100BASE with 2-port Gigabit combo Ethernet Switch



Highlights

+ Hardened-Grade for Non-Ventilated & Harsh Environments

Wide operating temperature range -40 to 75°C (-40 to 167°F)
Fanless operation
High impact, thermal shock, and electrical noise resistance

+ Compliance

EN 50121-4 certified for railway applications
NEMA TS2 rated
UL certified for safety

+ Management/Security Features

Port control
802.1x port-based network access control and remote authentication through RADIUS and TACACS+
Configure and monitor with eVue™ and eLite™

+ Support

Complimentary Technical Support
Free Firmware Upgrades
Limited Lifetime Warranty

Overview

EtherWAN's EX73000 Series is a hardened DIN-rail mounted managed Ethernet switch platform. Equipped with 16 10/100BASE-TX and 2 gigabit fiber ports along with Class 1 Div 2 certification, the EX73000 Series provides flexibility, speed, and reliability to support networks for hazardous locations and other areas where connectivity is crucial.

EtherWAN — "When Connectivity is Crucial."

Features

+ Interface

- CLI, Telnet, Web Browser
- SNMP v1/v2c/v3

+ Management

- Firmware upgrade
- Configuration backup via TFTP
- DHCP Server/Client
- RMON (Remote Monitoring): group 1, 2, 3, 9
- Port Mirroring: TX/RX and both
- NTP (Network Time Protocol) synchronization
- IEEE 802.1ab LLDP (Link Layer Discovery Protocol)
- IPv4/IPv6

+ Security

- MAC Address Filtering
- Enable/Disable port
- Storm control (Broadcast and multicast types)
- IEEE 802.1x LAN Access Control
- Remote authentication through RADIUS
- SSH for CLI and Telnet security
- SSL for web security
- System log (Remote/Local)
- Multi-level user account/password against unauthorized configuration

+ Quality of Service (QoS)

- Priority Queues: 4 queues per port
- Traffic classification based on IEEE 802.1p CoS, DSCP, WRR and strict mode
- Rate Limiting (Ingress/Egress)

+ Layer 2 Features

- Auto-negotiation for port speed and duplex
- Flow Control
- IEEE 802.3x Full duplex mode
- Back-Pressure half duplex mode

Redundant Protocols

- IEEE 802.1D STP
- IEEE 802.1w RSTP
- IEEE 802.1s MSTP
- EtherWAN's Alpha-Ring network fault recovery (<15ms)

VLANs

- Port-based VLANs
- IEEE 802.1Q Tag VLANs (128 groups, 4096 VID)
- GVRP
- GMRP

Link Aggregation

- Static Trunk (2 groups, support MAC base)
- IEEE 802.3ad LACP

IGMP Snooping v1/v2/v3

+ Performance

- Switching Capability
- 7.2Gbps

Specifications

+ Interface

Ethernet

16 x 10/100BASE-T(X)

0, 1 or 2 x Gigabit

Console

1 x DB9 RS-232

Alarm Contact

1 x Relay output, current capacity 0.6A/30VDC

LED Indicators

Per Unit: Power 1, Power 2

Per Port: Link/Activity (Green: Copper, Orange: Fiber)

+ Technology

Standards

IEEE 802.3 10BASE-T

IEEE 802.3u 100BASE-TX/100BASE-FX

IEEE 802.3ab 1000BASE-T

IEEE 802.3z 1000BASE-SX/1000BASE-LX

IEEE 802.3x Full duplex and flow control

IEEE 802.1p QoS

IEEE 802.1Q Tag VLANs

IEEE 802.1w RSTP

IEEE 802.1x PNAC

Forward/Filtering Rate

14,880pps for 10Mbps

148,810pps for 100Mbps

1,488,100pps for 1000Mbps

Packet Buffer Memory

12M bits

Processing Type

Store-and-Forward

Auto-negotiation

Half-duplex back-pressure and IEEE 802.3x Full-duplex flow control

Auto MDI/MDIX

Address Table Size

16K MAC Addresses

+ Power

Input

12-48VDC Redundant (Terminal block)

Power Consumption

8.06W 0.336A@24VDC

Protection
Reverse Polarity Protection

+ Physical

Casing Material
Aluminum

IP Rating
IP30

Dimensions
60 x 125 x 145mm (W x D x H)
2.56" x 4.92" x 5.71"

Weight
1.19kg

Installation Type
DIN-rail mounting

+ Environmental

Operating Temp.
-40 to 75°C (-40 to 167°F)
Tested @ -40 to 85°C (-40 to 185°F)

Storage Temp.
-45 to 85°C (-49 to 185°F)

Relative Humidity
5% to 95% (non-condensing)


+ Regulatory

ISO
Manufactured in ISO-9001 facility

EMI
FCC Part 15B Class A
EN 61000-6-4
EN 61000-3-2
EN 61000-3-3

EMS
EN 61000-6-2
EN 61000-4-2 (ESD)
EN 61000-4-3 (Radiated RFI)
EN 61000-4-4 (Burst)


Dimensions



Device
Ethernet Switch


Documentation
Quick Install Guide

Application



Software


Network Management [eVue™ Network Configuration and Monitoring Tool](#)
 Network Discovery [eLite™ Network Discovery and IP Configuration Tool](#)



The screenshot shows the EtherWAN eVue interface. At the top, there is a navigation bar with 'Home', 'Devices', 'Batch', 'Group', 'Events', and 'Settings'. Below this, the 'Device List' tab is active, displaying a table of network devices. To the right, the 'Topology' tab shows a network diagram with nodes and connections. Below the device list, there is a 'Latest Events' section with a table of system events.

IP	System Name	Group
192.168.50.12	EG99-5012	
192.168.50.62	EX709-5062	
192.168.50.254	R50	
192.168.50.11	EG99-5011	
192.168.50.63	EX74-5063	
192.168.50.14	EX779-5014	
192.168.50.61	EX71v2-5061	
192.168.50.44	EX71-5044	
192.168.50.64	EX73-5064	
192.168.50.34	EX739-5034	

Acknowledged	ID	Severity	Time	Service	Node	Message
✓	5107	Normal	6/28/2019, 9:50:35 AM	login	server	User 'admin' logged in.
✓	5106	Normal	6/27/2019, 10:00:50 AM	login	server	User 'admin' logged in.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Web 192.168.1.19 is down.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Telnet 192.168.1.19 is down.
✓	5104	Normal	6/24/2019, 1:12:34 PM	login	server	User 'admin' logged in.



The screenshot shows the eLite interface. At the top, there is a navigation bar with 'List Server', 'Firmware', 'Configuration', and 'Help'. Below this, there is a table listing IP addresses and their corresponding MAC addresses.

IP Address	MAC Address
192.168.50.22	00:e0:b3:50:22:00
192.168.50.31	00:e0:b3:50:31:00
192.168.50.72	00:e0:b3:50:72:00
192.168.50.55	00:e0:b3:50:55:00
192.168.50.23	00:e0:b3:50:23:00
192.168.50.73	00:e0:b3:50:73:00
192.168.50.44	00:e0:b3:50:44:00
192.168.50.64	00:e0:b3:50:64:00
192.168.50.43	00:e0:b3:50:43:00
192.168.50.62	00:e0:b3:50:62:00
192.168.50.71	00:e0:b3:50:71:00
192.168.50.24	00:e0:b3:50:24:00

Ordering Info

+ Model

EX73400-00B 16-port 10/100BASE-TX
EX73402-0YB 16-port 10/100BASE-TX + 2-port Gigabit (Combo)

* DIN-Rail mounting kit included.

+ Gigabit Fiber Options (Y)

1 10/100/1000BASE-TX (No Gigabit Fiber port supported)
3 Combo port: 10/100/1000BASE-TX with 1000BASE-SX (SC) - 550m
4 Combo port: 10/100/1000BASE-TX with 1000BASE-SX (SC) - 2Km
5 Combo port: 10/100/1000BASE-TX with 1000BASE-SX (ST) - 550m
A Combo port: 10/100/1000BASE-TX with 1000BASE-LX (SC) - 10Km
B Combo port: 10/100/1000BASE-TX with 1000BASE-LX (SC) - 20Km

+ Accessories

Hardened SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver
DIN-Rail Power Supplies	www.etherwan.com/products/din-rail-power-supply (*)
*Recommended Power Supply	HDR-30-24 30W 24VDC DIN-Rail Power Supply
EB-232	Configuration Backup and Restoration Tool

